






版 本	A	B
	C	D

NOTE:

- 1.MATERIAL:
HOUSING:NYLON UL 94V-0
CONTACT: BRASS
PLATING:TIN
TEMPERATURE:-20°C+85°C
2.SPECIFICATION:
SIZE:20 TO 29 CIRCUITS
VOLTAGE:50V
CURRENT:1.0A
CONTACT RESISTANCE:20mΩ MAX.
DIELECTRIC WITHSTANDING VOLTAGE:500V AC.



P.C.B Layout



DIMENSIONS(mm)

CKT.	Catalog Number	A	B	C
20	FC502-20H	26.40	19.00	21.00
21	FC502-21H	27.40	20.00	22.00
22	FC502-22H	28.40	21.00	23.00
23	FC502-23H	29.40	22.00	24.00
24	FC502-24H	30.40	23.00	25.00
25	FC502-25H	31.40	24.00	26.00
26	FC502-26H	32.40	25.00	27.00
27	FC502-27H	33.40	26.00	28.00
28	FC502-28H	34.40	27.00	29.00
29	FC502-29H	35.40	28.00	30.00

TOLERANCE (UNLESS SPECIFIED)		REV	A	DR. BY	MATERIAL
LINEAR	ANGLE	SHEET		胡三保	FINISH
X (±0.1)	X° (±1°)				
XX (±0.05)	X° (±0.1°)	SCALE			DATE
XXX (±0.005)	XX° (±0.01°)	UNIT	mm	APP. BY	PART NO
					FC502-XXH

坤特股份有限公司

QUEENTECH ELECTRONIC CO.,LTD

TITLE: P=1.0mm FFC/FPC CONNECTOR

DWG ND.